



Teknisk data

LCD Size:	8,4"
LCD Resolution:	800x600
Brightness (cd/m2):	220cd/m2
LCD contrast ratio:	50000
LCD Color:	262K
Pixel Pitch (mm):	0.213 x 0.213
Viewing Angle (H-V):	120 / 100
Backlight MTBF:	1200000:00:00
CPU:	AMD Geode™ LX 800 (500MHz)
Chipset:	AMD® LX800+CS5536
Memory:	Supports one 1GB (maximum) 333MHz or 400MHz DDR SO-DIMM
I/O:	2 x USB 2.0
	1 x RS-232 COM port
	1 x RS-232/422/485 COM port
	2 x RTL8100C for 10/100 Mbps
	1 x power switch
	1 x reset button
SSD:	CF Type II
Watchdog Timer	Software programmable supports 1~255 sec. System reset
Audio:	2 x AMP 1.5W(internal speaker)
Expansion Slot:	1 x Mini PCI, (Wireless LAN Module)
	1 x Bluetooth Module(USB Interface, Bluetooth V2.0)
HDD Drive Bay:	N/A
Optional GPRS Module (support GSM 850,EGSM 900,DCS 1800 & PCS 1900):	N/A
Construction Material:	ABS + PC Plastic front frame
LED Function:	1 x Power ON/OFF LED on front panel
Mounting:	Panel, Wall, Rack, Stand or Arm
Front Panel Color:	Gray
Dimension (WxHxD) (mm):	234(W) x 154(H) x 42(D) mm
Operating Temperature:	0 ~ 50° C
Storage Temperature:	-20~ 60° C
Net Weight	0.8kg
Vibration	5 ~ 17 Hz, 0.1" double amplitude displacement, 17 ~ 640 Hz, 1.5G acceleration peak to peak
Shock	10G acceleration peak to peak. (11ms)
IP Level(front panel):	IP 64 compliant
Safety & EMI:	EMC, CE, FCC, UL, CCC and CB
Touch Screen:	Resistive Type 4-Wire(touch controller IC is on board)
Power Adapter:	90V-260V AC@50/60 Hz
Power Requirement:	12VDC
Power Consumption:	20W